

Taixing EHE Composite Materials Co., Ltd

TA-2560

TA-5080

TA-5011

ITEM	SPECIFICATION		
APPEARANCE	The tape must be wrapped uniformly. The wick does not thrust out. The whole must not become like the bowl. Both sides must be flat. The color must be accordant. They must not dirt and wound.		
COLOR	Light yellow, dark yellow, blue, white, red, green, black, transparent, etc. Special colors can be customized for processing.		
DIMENSION	Total THICKNESS (mm)	0.06 ± 0.005 0.08 ± 0.005 0.11 ± 0.005	
	WIDTH (mm)	SPECIFIED WIDTH \pm 0.15	
	LENGTH (M)	66±0.5 50±0.5 50±0.5	
CHARACTERISTICS	BACKING		PET FILM
	ADHESIVE		Acrylic
	PEELING STRENGTH(N/M)		≥300
	PULL STRENGTH POWER (N/10mm)		≥40 ≥80
	ELONGATION (%)		≥80
	DIELECTRIC BREAKDOWN (KV)		≥3.8 ≥6.8
	HEAT RESISTANCE		130 ℃
	FLAME RESISTANCE		UL510
	SOLVENT RESISTANCE		ОК
	Environmental Compliance		SGS
STORAGE VALIDITY	25℃、65%RH		
UL File No.	E465056		
PERIOD OF VALIDITY (YEAR)	One year		